








# Important Information about the CE Labelling of our Everroll X-treme and Everroll Products

 <p><b>07 / EN 14041: 2004</b> <b>Notified Body No. 1658</b></p>	<p>BSW GmbH Am Hilgenacker 24 57319 Bad Berleburg Germany Tel. ++49 (0)2751 803 0 Fax ++49 (0)2751 803 109 Email info@berleburger.de Internet www.berleburger.de</p>	
<p><b>Everroll X-treme</b> <b>Thickness 4 mm</b> <b>Certificate No. 1658-BPR-1013</b></p> <p><b>EPDM 1100 B1 C<sub>fl</sub></b> <b>Certificate No. 1658-CPD-1127</b></p>	 <p>EN 13501-1</p>	 <p>EN 13893 &gt;0,3μ</p>
<p><b>Everroll X-treme</b> <b>Thickness &gt;4 – 8mm</b> <b>Certificate No. 1658-BPR-1014</b></p> <p><b>Everroll Uni, Stone</b> <b>Thickness 4 – 8 mm</b></p> <p><b>EPDM 1100</b> <b>Thickness 4 – 8 mm</b></p> <p><b>EPDM 1300</b> <b>Thickness 4 – 8 mm</b></p>	 <p>EN 13501-1 Fully adhered to massive mineral bases (Density: minimum ≥1350 kg/m³)</p>	 <p>EN 13893 &gt;0,3μ</p>
<p><b>Everroll Classic, Endurance, Vision, Star</b></p>	 <p>EN 13501-1</p>	 <p>EN 13893 &gt;0,3μ</p>